



■15-145kv TECHNICAL INDICATOR■

No.	Type	Rated voltage (kV)	Specified mechanical load(kN)	Section height (mm)	Minimum arcing distance (mm)	Minimum nominal creepage distance (mm)	Power frequency voltage \geq		Lightning impulse withstand voltage \geq	Weight (kg)
							Dry	Wet		
10201A	FXB1-10/70SD-325	10	70	325	170	340	66	55	100	1.07
10201B	FXB1-10/70WT-325	10	70	325	170	340	66	55	100	1.15
10201C	FXB1-10/7000-335	10	70	335	170	340	66	55	100	1.12
10201A.1	FXB1-10/70SD-360	10	70	360	205	420	85	70	125	1.12
10202A	FXB2-10/70SD-325	10	70	325	185	430	75	60	115	1.14
1020A.1	FXB2-10/70SD-360	10	70	360	220	535	90	70	135	1.21
10202B	FXB2-10/70WT-325	10	70	325	188	430	75	60	115	1.22
10202B.1	FXB2-10/40WT-326	10	40	326	220	535	90	70	135	0.98
10202A.3	FXB2-10/70DS-335	10	70	335	190	440	80	65	120	1.15
10202C	FXB2-10/7000-341	10	70	341	188	430	75	60	115	1.20
10202E.1	FXB2-10/70SD-379	10	70	379	220	535	90	70	135	1.31
10203A	FXB3-10/70SD-340	10	70	340	210	420	85	70	125	1.28
10203A.B	FXB3-10/100SD-366	10	100	366	210	420	85	70	125	1.77
10203B	FXB3-10/70WT-330	10	70	330	210	420	85	70	125	1.33
10203B.B	FXB3-10/100WT-363	10	100	363	210	420	85	70	125	1.61
10203C	FXB3-10/7000-340	10	70	340	210	420	85	70	125	1.29
10205A	FXB5-10/70SD-320	10	70	320	190	443	80	65	120	1.29
10205B	FXB5-10/70WT-310	10	70	310	190	443	80	65	120	1.27
10205C	FXB5-10/7000-326	10	70	326	190	443	80	65	120	1.24
10205G	FXB5-10/70DD-320	10	70	320	190	443	80	65	120	1.08
1020AA1	FXBW-10/70SD-370	10	70	370	245	600	100	70	140	1.38
1020AB1	FXBW-10/70WT-366	10	70	366	245	600	100	70	140	1.40
1020AG1	FXBW-10/7000-376	10	70	376	245	600	100	70	140	1.40
1020AK1	FXBW-10/70ST-370	10	70	370	245	600	100	70	140	1.29
24201A	FXB1-24/70SD-395	24	70	395	240	505	100	70	140	1.16
24201A.2	FXB1-24/70SD-465	24	70	465	310	665	115	90	165	1.25
24201E.1	FXB1-24/70SD-449	24	70	449	272	587	100	70	150	1.30
24201B.2	FXB1-24/70WT-465	24	70	465	310	665	115	90	165	1.34
24202A.2	FXB2-24/70SD-465	24	70	465	327	847	120	95	170	1.39
24202B	FXB2-24/40WT-360	24	40	360	260	637	100	75	150	1.05
24202C.1	FXB2-24/7000-446	24	70	446	293	740	100	75	155	1.38

Quality in Manufacturing, Excellence in Service!

AP/AR
PO Box 1128
Orange, CT 06477

Sales & Marketing
1088 Orange Avenue
West Haven, CT 06516

Warehouse
475 Elm Street
West Haven, CT 06516

Int'l Forwarding & Logistics
JFK International Airport
Jamaica, New York 11430



SMA/Shuimin AG
Standard Manufacturer for America

Tel: 1 (203) 933-7073
 Fax: 1 (203) 933-7074
 Toll Free: 1-877-233-2247
 Http: www.standardmanufacturer.com

24202B.2	FXB2-24/70WT-465	24	70	465	327	847	120	95	170	1.48
24202E.5	FXB2-24/70SD-458	24	70	458	307	760	115	90	165	1.36
24203A	FXB3-24/70SD-442	24	70	442	308	654	115	90	165	1.48
24203B	FXB3-24/70WT-432	24	70	432	308	654	115	90	165	1.50
24203C	FXB3-24/7000-442	24	70	442	308	654	115	90	165	1.47
24204A	FXB4-24/70SD-398	24	70	398	252	595	100	70	150	1.35
24204A.1	FXB4-24/70SD-452	24	70	452	296	707	100	75	155	1.45
24204B	FXB4-24/70WT-389	24	70	389	252	595	100	70	150	1.39
24204B.2	FXB4-24/70WT-476	24	70	476	340	822	120	95	170	1.54
24204C.1	FXB4-24/7000-442	24	70	442	296	707	100	70	155	1.44
24204C.2	FXB4-24/7000-486	24	70	486	340	822	120	95	170	1.51
24205A.1	FXB5-24/70SD-470	24	70	470	320	790	115	90	165	1.50
24205B.5	FXB5-24/70WT-422	24	70	422	290	770	100	75	155	1.49
24205N.5	FXB5-24/70SWD-431	24	70	431	290	770	100	75	155	1.58
2420AA	FXBW-20/70SD-422	20	70	422	300	750	100	75	155	1.47
2420AA.C	FXBW-24/120SD-454	24	120	454	300	756	100	75	155	2.0
2420AB.C	FXBW-24/120WT-451	24	120	451	300	756	100	75	155	1.79
2520AB.1	FXBW-25/40WT-314	25	40	314	228	545	90	70	135	1.02
2520AA	FXBW-25/80SD-358	25	80	358	228	545	90	70	135	1.32
2520AC	FXBW-25/8000-358	25	80	358	228	545	90	70	135	1.33
36201A.1	FXB1-36/70SD-535	36	70	535	380	830	125	95	200	1.35
36201B.2	FXB1-36/70WT-570	36	70	570	416	912	130	100	205	1.48
36201C.2	FXB1-36/7000-586	36	70	586	416	912	130	100	205	1.45
36202A.2	FXB2-36/70SD-570	36	70	570	434	1154	130	100	205	1.59
36202B.1	FXB2-36/70WT-535	36	70	535	399	1050	125	95	200	1.60
36202C	FXB2-36/7000-516	36	70	516	363	950	125	95	200	1.57
36203A	FXB3-36/70SD-560	36	70	560	415	902	130	100	205	1.69
36203B.C	FXB3-36/100WT-583	36	100	583	415	902	130	100	205	2.01
36203C	FXB3-36/7000-560	36	40	560	415	902	130	100	205	1.68
36204A	FXB4-36/70SD-530	36	70	530	384	935	125	95	200	1.61
36204B.1	FXB4-36/70WT-548	36	70	548	405	960	125	95	200	1.64
36204C	FXB4-36/7000-530	36	70	530	384	935	125	95	200	1.60
36205A.3	FXB5-36/70SD-550	36	70	550	389	1025	125	95	200	1.67
36205B	FXB5-36/70WT-520	36	70	520	373	1005	125	95	200	1.66
36205C.3	FXB5-36/7000-550	36	70	550	389	1025	125	95	200	1.66
33202A	FXB2-33/70SD-500	33	70	500	364	950	125	95	200	1.47
33205A	FXB5-33/70SD-530	33	70	530	373	1005	125	95	200	1.66
33205B.B	FXB5-33/100WT-550	33	100	550	373	1005	125	95	200	1.95
46203M	FXB3-46/120Y-590	46	120	590	375	825	125	95	200	3.16

Quality in Manufacturing, Excellence in Service!

AP/AR
PO Box 1128
Orange, CT 06477

Sales & Marketing
1088 Orange Avenue
West Haven, CT 06516

Warehouse
475 Elm Street
West Haven, CT 06516

Int'l Forwarding & Logistics
JFK International Airport
Jamaica, New York 11430



■220-500kv TECHNICAL INDICATOR■

No.	Type	Rated voltage (kV)	Specified mechanical load (kN)	Socket and ball size	Section height (mm)	Minimum arcing distance (mm)	Minimum nominal creepage distance (mm)	Power frequency voltage ≥		Lightning impulse withstand voltage (kV)	Weight (kg)
								Dry	Wet		
220201	FXBW1-220/100	220	100	16	2150	1900	6300	540	495	1000	10
220202	FXBW2-220/100	220	100	16	2240	1900	6300	540	495	1000	10
220203	FXBW3-220/160	220	160	20	2150	1900	6300	540	495	1000	13
220204	FXBW4-220/160	220	160	20	2240	1900	6300	540	495	1000	13
330201	FXBW1-330/100	330	100	16	2930	2600	9075	750	715	1425	15
330202	FXBW2-330/100	330	100	16	2990	2600	9075	750	715	1425	15
330203	FXBW3-330/160	330	160	20	2930	2600	9075	750	715	1425	18
330204	FXBW4-330/160	330	160	20	2990	2600	9075	750	715	1425	18
330205	FXBW5-330/210	330	210	20	2930	2600	9075	750	715	1425	18
330206	FXBW6-330/210	330	210	20	2990	2600	9075	750	715	1425	18
500201	FXBW1-500/100	500	100	16	4030	3600	11000	975	925	2050	22
500202	FXBW2-500/100	500	100	16	4450	4000	13750	975	925	2050	26
500203	FXBW3-500/160	500	160	20	4030	3600	11000	975	925	2050	23
500204	FXBW4-500/160	500	160	20	4450	4000	13750	975	925	2050	26
500205	FXBW5-500/180	500	180	20	4030	3600	11000	975	925	2050	23
500206	FXBW6-500/180	500	180	20	4450	4000	13750	975	925	2050	26
500207	FXBW7-500/210	500	210	20	4030	3600	11000	975	925	2050	23
500208	FXBW8-500/210	500	210	20	4450	4000	13750	975	925	2050	26
500209	FXBW9-500/240	500	240	24	4030	3600	11000	975	925	2050	26
500210	FXBW10-500/240	500	240	24	4450	4000	13750	975	925	2050	26
500211	FXBW11-500/300	500	300	24	4030	3600	11000	975	925	2050	25
500212	FXBW12-500/300	500	300	24	4450	4000	13750	975	925	2050	29
500213	FXBW13-500/400	500	400	28	4030	3600	11000	975	925	2050	30
500214	FXBW14-500/400	500	400	28	4450	4000	13750	975	925	2050	35

Quality in Manufacturing, Excellence in Service!

AP/AR
PO Box 1128
Orange, CT 06477

Sales & Marketing
1088 Orange Avenue
West Haven, CT 06516

Warehouse
475 Elm Street
West Haven, CT 06516

Int'l Forwarding & Logistics
JFK International Airport
Jamaica, New York 11430